

TRANSWAAG PRO

The proven classic with state-of-the-art technology for the safe way of whole blood donation

NEW!



- Low weight
- Automatic tube and bag indication
- Colour and signal lamp
- Graphic colour display
- Lithium-ion battery technology
- Data transfer via USB-Stick

Convincing technology!

Technical Data

- Dimensions (w x h x d): 180 x 215 x 370 mm
- Input voltage: 90 - 264 V; 47 - 63 Hz
- Operating voltage: 12 - 24 V, DC
- Weighing accuracy: max. +/- 1%
- Possible ambient temperature: -10°C to +40°C
- Weight: 2,4 kg



Mixing tray

- Holds conventional as well as inline blood bag systems
- Easy to remove and to clean

Tube clamp

- Protects fingers by enclosing clamp mechanism
- Automatic tube indication

Colour signal lamp

- Gives optical alarms and hints:
- flow alarm
 - max. collection time reached
 - shock weight
 - filling quantity reached

Graphic colour display

- Clear instructions guide the user through the donation process
- Continuous monitoring
 - collection time
 - blood quantity
 - target blood quantity
 - flow indicator
 - mains and battery operation
- Status line

Option menu

- Parameters of operation can be set individually

Housing

- Robust aluminium housing

TRANSWAAG PRO

Mains or battery powered blood mixing and weighing device for stationary and mobile donation. The operating system can be tailored to our customers' needs to accommodate all requirements for a safe and effective documentation of the blood donation process:

- Scanner reads all commonly used barcodes quickly and reliably
- Donation data can be stored on an external backup medium or host computer



Transport case TW PRO

- Charging of TW-Power-Pack Li-Ion possible even when transport case is closed
- Lightweight and solid plastic material
- Stackable
- Protects TRANSWAAG PRO during transport and allows the storage of wall power adaptor, TW-Power-Pack Li-Ion, scanner and USB-Stick



USB-Stick

- Replaceable medium for data storage



Scanner TW TOUCH 65 PRO

- Reads barcode data



Lithium-ion battery

- Allows mains independent operation for at least 25 hours or 100 donations
- Deep discharge protection
- Can be integrated in transport case
- Capacity indication
- Integrated charge regulator



Ordering Information

Order no.	Description
97.8700.105	TRANSWAAG PRO - with 1x interface for scanner, 2x USB, 1x RS 232, 1x RJ 45, 1x battery - allows mains independent operation, Lithium-ion battery technology - data transfer via USB-Stick, RS 232 and Ethernet
97.8700.233	TW-Power-Pack Li-Ion - lithium-ion battery with integrated charging unit - can be integrated in transport case - allows mains independent operation of TRANSWAAG PRO for at least 25 hours or 100 donations
97.8700.238	16 Port RS 232 interface module Communication with up to 16 TRANSWAAG PRO via serial interface at the host computer
97.8700.239	TW data cable RS 232, 2m Connection between TRANSWAAG PRO and host computer 9-pole socket on 9-pole socket
97.8700.243	Scanner TW Touch 65 PRO Robust impact-resistant, nonwearing barcode scanner
97.8700.261	Customised TW-Software Individual configuration of the standard software according to user requirements, e.g.: - configuration of the options menu - number of scan steps - data transfer online or via USB-Stick - communication with central host computer
97.8700.445	USB-Stick - mobile data carrier
97.8700.980	Calibration weight 500 g - precision weight class M1 for calibration of TRANSWAAG PRO
97.8700.985	Transport case TW PRO - charging of TW-Power-Pack Li-Ion possible even when transport case is closed - lightweight and solid plastic material - stackable - protects TRANSWAAG PRO during transport and storage and allows the storage of wall power adaptor, TW-Power-Pack Li-Ion, scanner and USB-Stick



Distributed by

SARSTEDT AG & Co.
P.O. Box 12 20
D-51582 Nümbrecht
Phone +49 2293 3050
Fax +49 2293 305-122
info@sarstedt.com
www.sarstedt.com